


SX, QF AND QFS

mm

規格	A 孔徑		B 外徑		C	E	F	G	定位螺絲	重量 (kg)	最高轉速 rpm
	最小	最大	SX	QF							
035	3	9.5	16.00	-	21	6.8	16.00	-	-	0.06	31000
050	6	14	27.40	-	44	16.0	27.40	6.5	M6	0.10	18000
070	9	19	35.00	-	51	19.0	35.00	9.5	M6	0.25	14000
075	9	24	44.45	-	54	21.0	44.45	9.0	M6	0.45	11000
090	9	24	53.80	-	54	21.0	53.80	8.7	M6	2.00	9000
095	9	28	53.80	64	64	25.5	53.80	11.0	M6	0.86	9000
100	12	35	64.50	77	89	35.0	64.50	11.0	M8	1.66	7000
110	15	42	85.00	97	108	43.0	85.00	19.0	M10	3.70	5000
150	15	48	96.00	112	115	45.0	96.00	22.0	M10	5.04	4000
190	19	55	115.00	130	133	54.0	101.60	22.0	M12	7.32	3600
225	19	60	127.00	143	153	64.0	108.00	29.0	M12	8.40	3600

kw

轉速	規 格									
	050	070	075	090	095	100	110	150	190	225
100	0.037	0.06	0.12	0.20	0.27	0.58	1.10	1.56	2.09	2.93
720	0.260	0.43	0.90	1.44	1.95	4.18	7.94	11.23	15.07	21.09
960	0.350	0.58	1.20	1.93	2.59	5.58	10.59	14.98	20.09	28.13
1440	0.530	0.87	1.80	2.89	3.89	8.36	15.88	22.46	30.14	42.20
2880	1.050	1.73	3.61	5.78	7.78	16.73	31.77	44.93	60.28	84.40
3600	1.320	2.17	4.51	7.22	9.73	20.91	39.71	56.16	75.35	105.50
額定扭矩 (Nm)	3.510	5.77	11.90	19.20	25.80	55.40	105.00	150.00	200.00	280.00



SX-星形橡膠 QF-環套形橡膠